

FUSO

CANTER



- Longer Durability
- Unmatched Versatility

- Lower Fuel Consumption
- Payload Flexibility

- Maximum Rugged Reliability
- Wide Cabin

### Aftersales support

Comprehensive aftersales solutions covering service, genuine parts, driver training, and certification. Additionally offered, mobile workshop services across the country.

Simba Corp. growth evolved

Buy Kenya, Build Kenya

MODEL	CANTER			
	FE71CBN4RB11	FE84CE6RB11	FE85CG6RB11	FE85CHZR11
MODEL CODE	FE71CBN4RB11	FE84CE6RB11	FE85CG6RB11	FE85CHZR11
DRIVE CONFIGURATION	4 x 2			
DIMENSIONS (mm)				
Wheelbase	2,500 mm	3,350 mm	3,850 mm	4,170 mm
Overall length	4,630 mm	6,030 mm	6,750 mm	7,210 mm
Overall height, approx	2,045 mm	2,220 mm	2,210 mm	2,220 mm
Overall width	1,695 mm	1,995 mm	2,035 mm	2,135 mm
Cab to rear axle	2,030 mm	2,825 mm	3,325 mm	3,645 mm
Cab to end frame	3,105 mm	4,305 mm	5,025 mm	5,460 mm
<b>WEIGHTS (kg)</b>				
Max G.V.W	4,700 kg	6,500 kg	7,200 kg	8,000 kg
Kerb weight	1,905 kg	2,320 kg	2,455 kg	2,585 kg
<b>CALCULATED PERFORMANCE</b>				
Max. Speed (km/h) (Speed limiter - 80kmph)	90 km/h			
Max. Gradeability (%)	58,0%	40,5%	34,5%	30,5%
Min. Turning circle diameter (m)	5,1m	6,0m	6,8m	7,3m
<b>ENGINE</b>				
Model	4D33-6A, 4,215cc			
Type	4 STORKE -Direct injection			
No. of cylinders	4- Inline			
Max. Power	83kW / 113ps @ 3200 rpm			

Max. torque	304Nm/1,600rpm				
Alternator	24 Volt Ac, 50 Amp				
Emission	Euro 1				
<b>DRIVE LINE</b>					
Clutch	Hydraulic control, Single dry plate				
Transmission	5 forward and 1 reverse speed				
<b>CHASSIS</b>					
Axle	Front	Reverse Elliot, I-beam type			
	Rear	Full floating type			
Tyres	Front	700 R16/12PR	205/ 85 R16	225/ 85 R16	750R16/14PR
	Rear	700 R16/12PR	205/ 85 R16	225/ 85 R16	750R16/14PR
Steering	Ball nut type integral type hydraulic Power Booster				
Suspension	Front	Laminated Leaf Springs with Shock Absorbers			
	Rear				
<b>BRAKES</b>					
Brakes (service)	Hydraulic with Vacuum Servo assistance, dual circuit				
Brakes (parking)	Internal expanding type on propeller shaft				
Brakes (auxiliary)	Exhaust brake				
<b>OTHERS</b>					
Fuel Tank Capacity	70 litres	100 + 70 litres			
Electrical system (batteries)	12Vx2, 52AH at 5hr/2, 65AH at 20hr				

**Fuso Authorized Distributor Simba Corporation**

**Simba Corporation Limited:**

**Nairobi 0703 046 000 | Mombasa 0703 046 400 | Kisumu 0703 046 620 | Kisii 0703 046 670/1 | Narok 0703 046 570**

**sales@simbacolt.com | www.simbacorp.com**



**Crater Automobile Ltd: Nbi: 0733 636188 | Nku: (051) 221 2055/6, Kis: 0724 747370, Eld: 0784 955398**

**Automobile Warehouse Ltd: Nku: (051) 221 2135, 0727 346 326, 0722 580843 | MT. Kenya Trucks Ltd: Meru: 020 785 0405 / 0701 888 786**

**Multi-Line Motors (Kenya) Ltd: Nbi: 0722 830 802, Thika: 0798 566986, 0780 440309 | Esso Motor Sales: Nanyuki: (062) 203 2621 | Plateau Motors Ltd: Machakos: 0722 777115**



**Manufactured by Simba Corporation.**

**Simba Corp.** growth evolved<sup>+</sup>