

TF-CANTER



- Longer Durability
- Unmatched Versatility
- Lower fuel consumption
- Maximum rugged reliability
- Comfort & Safety

Aftersales support

Comprehensive aftersales solutions covering service, genuine parts, driver training and certification. Additionally offered, mobile workshop services across the country.



SPECIFICATIONS					
MODEL	CANTER FE-51	CANTER FE-NC	CANTER FE-WC	CANTER FE-91	CANTER FE-X
MODEL CODE	FEA51BR4SB12	FEA51ER4SB12	FEC71ER4SB13	FEC91GR4SB13	FECX1HR4SB13
DRIVE SYSTEM	4 x 2	4 x 2	4 x 2	4 x 2	4 x 2
DIMENSIONS (mm)					
Wheelbase	2500	3400	3400	3850	4300
Overall length	4707	5785	5970	6685	7185
Overall width	1875	1875	2145	2145	2145
Overall height, approx.	2020	2020	2195	2215	2210
WEIGHT (kg)					
Max. G.V.W.	4700	5700	6500	7500	8550
Kerb Weight (Approx.)	2055	2120	2390	2475	2510
CALCULATED PERFORMANCE					
Max. Gradeability (%)	45%	37%	38%	38%	33%
Min.Turning circle diameter (mm)	5000	6600	6100	6500	7200
ENGINE					
Model	4P10-KAT2		4P10-KAT4		
Type	4 stroke-cycle, turbo intercooled direct injection diesel engine, 2998cc (common rail)				
No. of cylinders	4; in-line				
Max. Power	96kW/128hp @3500rpm		110Kw/147hp @3500rpm.		
Max. torque (Nm)	300 Nm @ 1300 rpm		370 Nm @ 1350 rpm		
DRIVE-LINE					
Clutch	Hydraulic control, single dry plate				
Transmission	5 forward and 1 reverse speed synchromesh gearbox				
TIRES AND WHEELS					
Tire and disc wheels,	Single front, dual rear		Single front, dual rear		

SPECIFICATIONS					
MODEL	CANTER FE-51	CANTER FE-NC	CANTER FE-WC	CANTER FE-91	CANTER FE-X
Tire Size	205/85R16	205/85R16	215/ 75R17.5		
Tube / Tubeless	Tubeless				
STEERING SYSTEM					
Steering column	Right hand steering. Ball nut type with hydraulic power booster				
SUSPENSION					
Front spring	Laminated leaf springs with shock absorbers and stabilizer				
Rear spring	Laminated leaf springs with shock absorbers				
BRAKES					
Service brakes	Hydraulic with vacuum servo assistance, dual circuit with ABS+EBD				
ABS+EBD	Standard				
Auxiliary brake – Exhaust					
ELECTRICAL SYSTEM					
System Voltage	12 volt				
FUEL TANK					
Main tank capacity (Lockable)	70L	100L		100L +70L	
CAB					
Type	All steel, tilt cab - Standard		All steel, tilt cab - Wide		
EXTRA FEATURES					
A/C (Manual Air conditioner)	Radio player				
Key loss prevention buzzer	Storage compartments				
Power window					
Hill start					
SRS Airbag for Driver					
Central door lock & Keyless entry					

HILLSTART ASSIST



ABS + EBD



SRS AIRBAG FOR DRIVER



SPACIOUS CABIN



FUSO

SIMBA CORPORATION LIMITED (BRANCHES)

Nairobi 0703 046 000 | **Mombasa** 0703 046 400 | **Kisumu** 0703 046 652
Kisii 0703 046 670/1 | **Nyeri** 0703 046 686
simbacares@simbacolt.com | www.simbacorp.com

Simba Corp. growth evolved⁺

DEALERS:

Crater Automobiles (NBI) Ltd: **Nbi:** 0733 636188 | **Nku:** 0725 212055/56 | **Kis:** 0724 747370 | **Eld:** 0784 955398 | Automobile Warehouse Ltd: **Nku:** (051) 221 2135, 0727 346 326, 0722 580843
MT. Kenya Trucks Ltd: **Meru:** 020 785 0405 / 0701 888 786 | Multi-Line Motors (Kenya) Ltd: **Nbi:** 0722 830 802 | Jeet Investments 2017 Ltd: **Kericho:** (+254) 722 284 910
Plateau Motors Ltd: **Machakos:** 0722 777115 | ASMI Motors Limited: **Marsabit:** 0705 806 756. | Westfield Motors Limited: **(Kitale)** – 0721 461 159/0736 731 343 , **(Kakamega)** - 0721 934 987/ 0736 474 720

MITSUBISHI FUSO Authorized Distributor
Simba Corporation Ltd
www.fuso.co.ke

*Available for Leasing. T&C's Apply.

Manufactured by Simba Corporation Ltd